

Flash Unit		HS	TTL	Power Control	Power Display on Transmitter	Triggering
Quadra★ 1st series	Action (A)	●	✗	✓	✗	✓
	Pro (S)	●				
Quadra RX★ 2nd series	HS	●	✗	✓	✓	✓
	RQ Ringflash Pro	●				
Quadra Hybrid AS RX★ 3rd series	RQ Ringflash Pro	●				
ELB 400★	RQ Ringflash Eco	●	✗	✓	✓	✓
ELB 500 TTL	ELB 500 Head	●	✓	✓	✓	✓
Ranger RX (Speed and Speed AS) with Transceiver RX	A	●	✗	✓	✗	✓
	S	●				
ELB 1200★	Action	●				
	Pro	●	✗	✓	✓	✓
	HS	●				
D-Lite it	2	●	✗	✗	✗	✓
	4	●				
D-Lite RX	ONE / 2	●	✗	✓	✓	✓
	4	●				
BXRi	250 / 500	●	✗	✓	✗	✓
BRX	250 / 500	●	✗	✓	✓	✓
ELC Pro HD	500	●	✗	✓	✓	✓
	1000	●	✗	✓	✓	✓
Style RX with Transceiver RX	300 / 600	●	✗	✓	✗	✓
	1200	●				
Digital RX 1200 Digital RX 2400 with Transceiver RX	Zoom Action	●				
	Zoom Pro	●	✗	✓	✗	✓
	Zoom Pro HD	●				
	Ringflash 3000	●				
Universal Receiver★		●	✗	✗	✗	✓
Receiver Plus★		●	✗	✗	✗	✓

★ We recommend using a slow flash duration (output A on units).

● Recommended.

● Not optimised.
High shutter speeds might produce unexpected results depending on the flash unit, power levels, camera model and sensor size.

● Not compatible.

✓ Feature available.

✗ Feature not available.